



ELECTRIC POWERTRAIN SOLUTIONS

SMAC SERIE

TECHNICAL DATA SHEET

3-PHASE SYNCHRONOUS MOTOR

Code	51J20021019ET080400		
Rev.	01		
Date	03/03/2021		
Page	1	di	2


Motor Rated Power			10000W	
--------------------------	--	--	---------------	--

Inverter Power Supply			48Vdc	
------------------------------	--	--	--------------	--


Description	Symbol	Unit		
Duty	-	-	S2-60min	
Nominal Speed	n_n	rpm	1000	
Frequency (N° poles)	$f (2p)$	Hz	66.6 (8)	
Costant Voltage	K_e	Vrms/Krpm	26.0	
Costant Torque	K_t	Nm/Arms	0.43	
Instant Torque	T_i	Nm	245.0	
Instant Current	I_i	Arms	660.0	
Peak Torque	T_p	Nm	175.0	
Peak Current	I_p	Arms	440.0	
Rated Torque	T_r	Nm	95.0	
Rated Current	I_r	Arms	230.0	
Rotor Inertia	J_r	kg x m ²	0.036	
Ambient Temperature	θ_a	°C	-15 ÷ +40	
Protection Degree	IP		IP 54	up to IP67
Insulation Class	-	-	F	
Thermal protection	-	-	KTY 84-130	
Cooling system			Air	

Speed-Torque & Speed Power Motor Curves (*)

SMAC 200-210



Efficiency Map % (*)



* MTPA Field Weakening strategy control & Optimized Advance Angle